



Features

- Surface or Suspended LED Linear luminaire with Louvre + Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1160x187x47mm, Sylvania White body colour, IP20, IK07, Light Engine Dimensions: 1130x165mm, Constant Current, Low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 6770lm, 53W, 128lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<19, Luminance at 65° < 3000 cd/m², Lumen Maintenance: L90B10 at 50,000 hours, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.

Product Overview

Product name	RANA LED S 1200 HO HSX 4K LOUV+PRI W GEN2
Technology	LED
Housing	Steel
Mount	Ceiling surface mounting,Suspended
General application	Education,Hospitality,Office,Retail
Fixture luminous flux (lm)	6770
Luminous flux (lm)	6770
Luminaire efficacy (lm/W)	128
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 19
Photobiological Risk Group	RG0
Total power consumption (W)	53
Electrical protection	Class I
Control gear type	LED driver constant current

RANA LED S 1200 HO HSX 4K LOUV+PRI W GEN2

0097972

Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK07
Product EAN number	5410288979724